

PROJECT	NOTES	TYPE	DATE	CAT. No.
---------	-------	------	------	----------



# EM2-RDL

## Emergency Battery Backup for 7" & 12" LED Disk Light

Emergency operation of your lighting package is a simple decision with Integral Emergency Back-Ups in a surface mount collar. The EM2-RDL accessories can be installed during the final stages of construction or remodel. With use with product line RDL series that includes "EMTB". \*Light fixture sold separately



OUTPUT VOLTAGE	120V	LED Emerg Output Current	100mA-700mA
INPUT FREQUENCY	50/60 Hz	LED Output Protection	Self Resetting PTC
RECHARGE TIME	24-48 HRS	Illumination Time	90 min
INPUT CURRENT	0.07A	Output Power	8W (7"), 15W (12")
INPUT VOLTAGE	100-277VAC	DIMMING	N/A
OUTPUT CLASSIFICATION	UL924/Class2	OPERATING TEMP.	-25--+55C
COMPATIBLE BATTERIES	LiFePo4, NiCd, 9.6VDC	BEAM ANGLE	N/A

### ORDER INFO / EXAMPLE: EM2-RDL-7-WH

SERIES	DIAMETER	FINISH
EM2-RDL	7	WH
EM2-RDL Emergency Battery Backup for LED Disk Light  *Disk Light Sold Separately (Refer to RDL Spec Sheet)	7-7" 12-12"	BL- Black BN- Brushed Nickel WH- White ORB- Oil Rubbed Bronze